

MP-Systems EFO Series

Performance Features:

- 3 GPM - up to 1000 PSI
- Patented Hydracell Pump
- Oil or Water Based Coolants
- Dual Voltage Standard
- Portable with Rolling Castors
- Durable Powder Coat Finish
- Feed Pump Standard



High Pressure Coolant System

Model EFO



Filtration Features Include:

- 5 Micron Filtration
- Dirty Filter Alarm Standard
- Quick Change Filters



MP-Systems - September 2008

MP-Systems
17F Herman Drive
Simsbury, CT 06070
Toll-free 877.689.1860
www.mp-systems.net

EFO Series Specifications

Model EFO	
Fluid Type	Oil or Water
Max. Pressure	Up to 1000 PSI (70 Bar)
Max. Flow Rate	3 GPM (11.3 l/m)
Flow Rate Type	Fixed Volume
No. of Ports	1
Filtration	5 micron Single Filter
Main Motor HP	2 (2.7 kw)
Voltage	208/230/460/3/60
Feed Pump	Standard
Dirty Filter Alarm	Standard
Footprint (L x W x H)	23.15" x 15.10" x 17.75"
Weight lbs	200

Options

Option	P/N	Description
Line Kit	VKP-073A	Inlet/return lines, fittings, electrical connectors
Spare Filter Bag	MP4	#4 replacement 5 micron bag
Installation	Install	Basic install to machine tool

Notes

1. Recommended for pumping cutting fluids up to 140 SSU @ 100° F.
2. Confirm spare M codes
3. Specifications are subject to change without prior notice



MP-Systems
17F Herman Drive
Simsbury, CT 06070
Toll-free 877.689.1860
www.mp-systems.net

For service call 1-877-689-1860 or e-mail service@mp-systems.net